

Essential Cat5e Patchcords

- Complies to the latest Category 5e standard
- Light grey PVC
- Screened and unshielded
- Moulded strain relief boot

Description

Application

Nexans Essential patchcords are intended to be used to complete the installation of an "Essential" Category 5e system.

- Flexible grey PVC.
- Moulded strain relief boot.
- 1.5m and 3m standard lengths.



essential

Contact

LAN Systems (Nexans Cabling Solutions)
2 Faraday Office Park, Faraday Road
RG24 8QQ Basingstoke
United Kingdom
Phone: +44 (0) 1256 486640
ncs.uk@nexans.com



Flame retardant
IEC 60332-1

Essential Cat5e Patchcords

Characteristics

Construction characteristics	
Colour	Grey
Outer sheath	PVC
Dimensional characteristics	
Nominal outer diameter (mm)	6.35 mm
Electrical characteristics	
Characteristic impedance	100 Ohm
Usage characteristics	
Mechanical durability/matings	100
Range	essential
Flame retardant	IEC 60332-1
Category	Cat. 5e

Product List

Nexans ref.	Name	Screen	Length (m) (m)
N101.122DG	Essential Patchcord F/UTP Cat5 1,5m PVC grey	Yes	1.5
N101.122FG	Essential Patchcord F/UTP Cat5 3m PVC grey	Yes	3
N101.112DG	Essential Patchcord U/UTP Cat5 1,5m PVC grey	No	1.5
N101.112FG	Essential Patchcord U/UTP Cat5 3m PVC grey	No	3